



Technical Data Sheet

PRO-766

DESCRIPTION:

PRO-766 is a pre-finished parquet adhesive for indoor, above grade use.

PHYSICAL CHARACTERISTICS:

Description:	formulated polyvinyl acetate emulsion
Colour:	tan
Odour:	mild. Typical of polymers.
Total Solids:	66%-70%
pH:	6.0-7.5
Relative Density:	1.36 ± 0.01
Cleaning	tepid water
Storage:	6 months under normal conditions. Keep from freezing. Do not stack pallets more than 2 high.

DIRECTIONS FOR USE:

For indoor above grade use only. Not recommended for kitchens, bathrooms, laundry rooms, or other damp areas. For bare wood or bare concrete sub-flooring only. Subfloor must be absolutely clean, level, smooth, well cured and completely dry.

Should be applied at normal room temperature. Above 18°C (65°F). Leave a minimum expansion space of 1.27cm (1/2") wide next to all walls and around fixed objects.

Use a V notched trowel 1/8" x 1/8" x 1/8". The adhesive is spread on a limited area of 0.5 metres x 1 metre (1.5 ft. x 3 ft.) and the parquet sheets are immediately pressed firmly into place. An adequate amount of adhesive should be used to ensure proper adhesion of each slat. 3.78 litres covers approximately 9.5 square metres (100 sq. ft.) There must be intimate contact between the surfaces being glued and the adhesive should be wet when the parquet sheets are laid down. Use tepid water for cleaning. Allow a 24 hours drying period before proceeding with other work.

KEEP OUT OF REACH OF CHILDREN
